

#### **Product Data Sheet**

### Cee-Bee® E-2787

**Cee-Bee® E-2787** is an environmentally friendly paint stripper designed to remove topcoat of selectively strippable systems.

# 👷 Conforms To

- Boeing
  - o BMS 11-13
- Military
  - o T.O. 1-1-24 (Non-Metallic)

### 🔱 Benefits

- Contains no halogenated solvents, phenol, heavy metals or other toxic materials (per Proposition 65).
- Designed to remove topcoat of selectively strippable systems.
- Thixotropic. Clings to vertical, inclined and overhead surfaces.
- Slow drying for a long reaction time.
- Free rinsing.
- Safe on all aircraft structural metals, including high strength steel.
- Surfactants are biodegradable.

## Properties

- Thick liquid
- Opaque color

Mild odor

### **Notes Prior to Handling**

Before using your Cee-Bee<sup>®</sup> products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee<sup>®</sup> representative before proceeding.



### ᅌ Use Procedure

Use a high pressure 10:1 or 5:1 air-activated pump equipped with a  $\frac{1}{2}$ " I.D. high pressure hose and spray wand with a fan type spray nozzle. It is very important to use the correct type of spray nozzle for this application. Contact your Cee-Bee<sup>®</sup> representative for pump and nozzle assistance.

It is also very important to apply the stripper at the correct pressure. Use a pump inlet pressure of 80 to 110 P.S.I. Optimum performance is attained at a temperature of about 75-87°F (24-31°C).

- 1. The surface to be stripped should be thoroughly clean and free from water.
- 2. Spray on a light coat of Cee-Bee<sup>®</sup> E-2787 starting from the bottom of the aircraft and working upward. Apply the stripper as evenly as possible.
- 3. Keep the surface wet with stripper until the paint buckles.
- 4. When the paint is lifted (one hour to overnight for tough coatings), brush the surface thoroughly to remove the loosened paint.
- 5. Reapply stripper as required to loosen any remaining paint.
- 6. When all of the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual stripper.
- 7. Thoroughly rinse the surface with high-pressure water.

#### Safety, Handling, and Precautions

- Some form of eye protection is always absolutely essential when working with any chemical.
- Product may irritate eyes and skin. Use goggles, gloves and other protective clothing sufficient to avoid contact.
- Concentrated vapors may cause irritation. Use in well ventilated area.
- For contact with eyes or skin, flood with water immediately. Seek medical attention if irritation persists.
- Proper attention should always be paid to environmental considerations.



#### **Product Data Sheet**

#### **Contact Us**

#### **United States**

**McGean** Phone: +1-216-441-4900 Fax: +1-216-441-1377 Email: <u>Aviation@McGean.com</u> United Kingdom McGean-Rohco (UK) Ltd. Phone: +44-1902-456563 Fax: +44-1902-457443 Email: <u>Aviation@McGean-Rohco.co.uk</u>

Singapore McGean Singapore Phone: +65-6863-2296 Fax: +65-6863-2297 Email: Info@ceebee.com.sg **China Cee-Bee Aviation Materials (Xiamen) Co. Ltd.** Phone: +86-592-551-3689 Email: Info@ceebee.com.cn

**Cee-Bee® E-2787** is an environmentally friendly paint stripper designed for removing polyurethane and other paint systems.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)