

Product Data Sheet

Cee-Bee[®] E-2013T

Cee-Bee[®] **E-2013T** is an environmentally friendly hot tank-type remover for polyurethane and other paint systems.

👷 Conforms To

- Military
 - o MIL-PRF-83936



- Contains no halogenated solvents, phenol, heavy metals or other toxic materials (per Proposition 65).
- Safe on all aircraft structural metals, including high strength steel, cadmium plated steel, mild steel, aluminum, and magnesium.
- Surfactants are biodegradable.

i Properties

- Yellow to Dark Brown Liquid
- Thin Liquid

• Mild Solvent Odor

Notes Prior to Handling

Before using your Cee-Bee[®] products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee[®] representative before proceeding.



Product Data Sheet

ᅌ Use Procedure

Cee-Bee[®] E-2013T may be contained in tanks fabricated of 300 series stainless steel, polyurethane or polyethylene. Use full strength at 140-160°F (60-70°C)

- 1. Immerse parts completely into lower layer and soak until the coating has been penetrated and loosened.
- 2. When the coating is satisfactory loosened, withdraw the parts and drain over the tank.
- 3. Remove loosened paint with high pressure, air-boosted water. **Do not rinse over the process tank**. Removal may be assisted by agitating the surface with stiff bristle brushes.
- 4. Reimmerse parts in the tank to remove residual paints adhering to the surface, if residues are not removed after a suitable dwell time, an appropriate media blast procedure can be employed.

NOTE:

• Bath life can be extended by keeping the tank covered and by periodic desludging to remove paint residues.



Solution Control

• Maintain 6"-8" Oil Seal. Adjust if necessary with Cee-Bee® Additive O.

Safety, Handling, and Precautions

- May irritate eyes and skin.
- Use goggles, gloves, and other protective clothing sufficient to avoid contact.
- Concentrated vapors may cause irritation. Use in well ventilated area.
- For contact with eyes or skin, flush with water. If irritation persists, seek medical attention.



Product Data Sheet

Contact Us

United States

McGean Phone: +1-216-441-4900 Fax: +1-216-441-1377 Email: <u>Aviation@McGean.com</u> United Kingdom McGean UK Phone: +44-1902-456563 Fax: +44-1902-457443 Email: <u>Aviation@McGean-Rohco.co.uk</u>

Singapore McGean Singapore Phone: +65-6863-2296 Fax: +65-6863-2297 Email: Info@CeeBee.com.sg **China Cee-Bee Aviation Materials (Xiamen) Co. Ltd.** Phone: +86-592-551-3689 Email: Info@CeeBee.com.cn

Cee-Bee® E-2013T is an environmentally friendly hot tank-type remover for polyurethane and other paint systems.

CAUTION: Before using any of these products, you must become completely familiar with the safety and hazard information contained in our safety data sheets regarding these products. McGean-Rohco, Inc. (the seller) presents the information contained herein without warranty and disclaims any liability from its use or misuse. Seller recommends use of the information Seller's products solely in commercial processes which are specified by Seller and which do not violate any third party patent rights or any laws or regulations. The seller makes no warranties, express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose except as expressly stated in the seller's sales contract or sales acknowledgement form.

Cee-Bee Innovative Aviation Chemistry

Revision: A2 (9/16/2021)